



DATA SHEET

Effective August 07, 2026

Product Overview

Jazz® is an innovative rubber flooring that replaces the traditional vinyl type flooring in commercial and domestic applications, as well as being a popular choice in fitness and rehab applications. It offers great underfoot comfort, absorbs walking noise and has excellent non-slip properties. Jazz® comes in a range of compositions of synthetic (using EPDM rubber) and recycled product (using recycled tyre rubber). Thicknesses of 3mm, 5mm and 8mm are available with varying suitabilities of use.

With a high recycled content and ecologically responsible manufacturing processes, Jazz® flooring is the environmentally conscious flooring option for both designers and specifiers.

Specifications

Roll Width	1.1m	Thicknesses	3mm, 5mm, 8mm
Roll Length	5.5L/m 12.5L/m Full log*	Slip Resistance (AS/NZ 4586:2013)	Wet Sealed: P3 Wet Unsealed: P4 Dry Friction Sealed: D1 Dry Friction Unsealed: D1
Temperature Range	-25°C to 80°C	Hardness (Shore A)	50-60 ± 15%
Impact and Sound Reduction	$\Delta Lw = 16dB$, $L_{n,w} + C_i = 61$ tested at 3mm minimum (EN ISO 140-8)	Tolerance	Roll width ± 2% Roll length ± 4% Thickness ± 1mm Density ± 15%
Tensile Strength	1.40N/mm ² (ASTM D412)	VOC Emissions Certification Office Design IEQ-13 Office Interiors IEQ-11	Total Volatile Organic Compound emission rate 0.2mg/m ² /hr (24 hours)

* Full log yield dependent on thickness, see table below. Full logs may be cut and rolled into requested lengths - minimum 5L/m, maximum 16L/m.

Jazz® | Essentials Range

Material	Polymerically bound recycled rubber and EPDM	Composition	10% EPDM and 90% recycled rubber
Density	1150kg/m ³	CRF Fire Rating	2.6kW/m ² (ASISO 9239.1-2003)

Jazz® | Fugue

Material	Polymerically bound recycled rubber and EPDM	Composition	70% EPDM and 30% recycled rubber
Density	1400kg/m ³	CRF Fire Rating	2.6kW/m ² (ASISO 9239.1-2003)

Jazz® | Requiem

Material	Polymerically bound recycled rubber and EPDM	Composition	50% EPDM and 50% recycled rubber
Density	1300kg/m ³	CRF Fire Rating	2.6kW/m ² (ASISO 9239.1-2003)



National Sales and Technical Support:
(07) 3807 3666
sales@a1rubber.com
www.a1rubber.com



**UPCYCLED
AUSTRALIAN
TYRES**



DATA SHEET

Effective August 07, 2026

Appearance: Flat sliced surface with fine sliced texture. Can have recycling process contaminants and other fine impurities embedded throughout the surface.

Appearance of black can be varied depending on light and reflection, with increased light resulting in a lighter appearance of black. When reflective light is removed, blacks will appear uniform. Blacks will also appear more uniform over time with useage and scuffing that results in the surface becoming less reflective.

Shutter marks are minor surface impressions or lines left during the manufacturing process. On recycled rubber flooring they can appear as:

- Fine straight lines or slight ridges.
- A faint pattern from the mould or production equipment.
- Cosmetic marks only—they do not affect the performance, durability, or warranty of the product.

Because A1 Rubber products are manufactured using recycled rubber granules under high pressure, slight shutter marks and colour variations are considered acceptable.

Log Yield Range*	3mm	5mm	8mm
L/m	145L/m	86L/m	50L/m
m ²	160m ²	95m ²	55m ²

Applications

All Jazz® floors are monolithic in construction without veneers or laminates and are quick and easy to install. Jazz® floors are suitable for many different flooring applications, such as retail shops, walkways, gyms, sports centres, offices, schools, night clubs and rumpus rooms. Consult your supplier for the correct thickness and Jazz® floor type to suit each application.

Disclaimer

The above information is derived from periodic tests taken on actual product from the manufacturing process. Some variances in specifications and raw surface appearances are possible due to the use of recycled materials and our manufacturing tolerances. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The recommendation relating to the application and end use of A1 Rubbers™ products, are given in good faith, based on A1 Rubbers™ current knowledge and experience of the product when properly stored, handled and applied under normal conditions in accordance with A1 Rubbers™ recommendations. The user of the product must test the product's suitability for intended application and purpose. A1 Rubber™ reserves the right to change the properties and tolerances of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current Terms and Conditions of Sales and delivery. Users must refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

Document No. JAZZAUG26DATA



National Sales and Technical Support:
 (07) 3807 3666
 sales@a1rubber.com
www.a1rubber.com



**UPCYCLED
AUSTRALIAN
TYRES**