



# DATA SHEET

Effective February 13, 2025

## Product Overview

Used extensively in Australia for wetpouring various surfacing applications, A1 Rubber's™ CSBR® pre-coloured rubber has cleaned up the job environment of trowelling down rubber. No longer do applicators go home covered in oxide. CSBR® virtually eliminates those unsightly colour variations between batches.

CSBR® is available in 18 colours and is made in batches of 9 tonnes so jobs up to 900m<sup>2</sup> can be laid from the one batch.

## Specifications

<b>Particle Sizes</b>	1-4mm	<b>Density</b>	Loose Granules - Approx 500kg/m <sup>3</sup> Troweled Granules - Approx 700kg/m <sup>3</sup>
<b>Coating Type</b>	Milled pigments in baked on polyurethane	<b>Pack Size</b>	20kg perforated, UV treated plastic valve sacks
<b>Approx Coverage</b>	Granules - 1.7m <sup>2</sup> @ 15mm / 2.4m <sup>2</sup> @10mm on flat sub-base	<b>Sieve Analysis</b>	<2.0mm - 15% <4.0mm - 85%
<b>Colour Fastness</b>	See UV resistance document.		

**Note:** Aromatic binder has a temporary yellowing effect on all coloured rubber, this will usually burn of in around 6-8 weeks depending on season and locality. Generally it will make the colours look a little darker before returning to the original colour. This a natural process. The colours that can appear to have changed are mostly lighter blues and greys, such as CSBR Grey and Mid Blue.

## Applications

Used extensively in Australia for wetpouring various surfacing applications such as, playgrounds, walkways, outdoor areas and non-slip surfaces.

## Colours



\*Included colours are batch specific and may vary from this image.

### Disclaimer

The above information is derived from periodic tests taken on actual product from the manufacturing process. Some variances in specifications and raw surface appearances are possible due to the use of recycled materials and our manufacturing tolerances. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The recommendation relating to the application and end use of A1 Rubbers™ products, are given in good faith, based on A1 Rubbers™ current knowledge and experience of the product when properly stored, handled and applied under normal conditions in accordance with A1 Rubbers™ recommendations. The user of the product must test the product's suitability for intended application and purpose. A1 Rubber™ reserves the right to change the properties and tolerances of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current Terms and Conditions of Sales and delivery. Users must refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

Document No. CSBRFEB25DATA



**National Sales and Technical Support:**  
(07) 3807 3666  
sales@a1rubber.com  
[www.a1rubber.com](http://www.a1rubber.com)



**UPCYCLED  
AUSTRALIAN  
TYRES**