



DATA SHEET

Effective August 04, 2020

Product Overview

Duralast recycled rubber matting offers the end user significant cost savings over virgin rubber matting. From horse floats to automotive uses the Duralast range of thicknesses will cover every application.

Duralast rubber matting provides superior qualities of slip resistance, foot and leg anti-fatigue, durability and versatility.

Duralast is not permeable and is made from polymerically bound recycled rubber. For most applications requiring adhesion to the substrate we recommend single part polyurethane adhesives, and PU Kit 2 part adhesives for extreme applications.

Specifications

Material	Polymerically bound recycled rubber
Tensile Strength	1000 Density - 8.74 N/mm ²
Thickness	3mm, 5mm, 8mm and 10mm
Roll Length	10L/m - longer rolls are available on request
Roll Width	1.2m
Tolerances	Roll width - ± 1.5% Roll length - ± 1.5% Thickness - ± 1.0mm Density - ± 5.0%
Density	1,000kg/m ³
Shore A Hardness	1000 Density - 60
Wet Slip Resistance	P5 (V)
Dry Floor Friction	D1 ≥ 0.40 (F)
VOC Emissions Certification	
Office Design IEQ-13	Total Volatile Organic Compound emission rate 0.2mg/m ² /hr (24 hours)
Office Interiors IEQ-11	
Appearance	Flat sliced surface with fine sliced texture. Can have recycling process contaminants and other fine impurities embedded throughout the surface.

Applications

Duralast uses include all industrial and general rubber sheet applications, vibration dampening pads, acoustic control under concrete slabs, industrial flooring, truck, ute and horse float floors, load securement friction matting for pipes and sensitive freight, anti slip and anti fatigue matting, barbell flooring, mud flaps and ballast membranes to name a few.

Disclaimer

The above information is derived from periodic tests taken on actual product from the manufacturing process. Some variances in specifications and raw surface appearances are possible due to the use of recycled materials and our manufacturing tolerances. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The recommendation relating to the application and end use of A1 Rubbers products, are given in good faith, based on A1 Rubbers current knowledge and experience of the product when properly stored, handled and applied under normal conditions in accordance with A1 Rubbers recommendations. The user of the product must test the product's suitability for intended application and purpose. A1 Rubber reserves the right to change the properties and tolerances of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current Terms and Conditions of Sales and delivery. Users must refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

Document No. DUR AUG20DATA



National Sales and Technical Support:
(07) 3807 3666
sales@a1rubber.com
www.a1rubber.com



**UPCYCLED
AUSTRALIAN
TYRES**