



## DATA SHEET

Effective August 08, 2024

### Product Overview

Olympact™ underpads are used in applications where it is essential that the flooring system is able to absorb severe impact and high traffic noise. Olympact™ underpads are manufactured at 500kg/m<sup>3</sup> density to offer the correct underfoot stability needed when installed in conjunction with our Impact Tiles or our resilient 8mm Jazz® commercial flooring. Olympact™ can be layered to suit the acoustic needs of any application. Olympact™ products have been extensively on-site tested in numerous centres and buildings, and have successfully reduced the transmission of structure borne regenerative noise vibration from the typical activities performed in gymnasiums, school halls, under screeds and high traffic areas.

### Specifications

#### Tiles

|            |   |
|------------|---|
| Material   | Polymerically bound black recycled rubber |
| Appearance | Black                                     |
| Density    | 500kg/m <sup>3</sup>                      |
| Thickness  | 15mm, 20mm, 25mm, 30mm, 40mm              |
| Dimensions | 1m x 1m                                   |
| Tolerance  | Dimensions - ± 1.5%                       |
|            | Density - ± 5%                            |
|            | Thickness - ± 5%                          |

### Applications

Suitable for all gymnasium and other flooring applications where severe impact noise absorption is required for both above floor and below floor ambience.

#### Disclaimer

The above information is derived from periodic tests taken on actual product from the manufacturing process. Some variances in specifications and raw surface appearances are possible due to the use of recycled materials and our manufacturing tolerances. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The recommendation relating to the application and end use of A1 Rubber™s products, are given in good faith, based on A1 Rubber™s current knowledge and experience of the product when properly stored, handled and applied under normal conditions in accordance with A1 Rubber™s recommendations. The user of the product must test the product's suitability for intended application and purpose. A1 Rubber™ reserves the right to change the properties and tolerances of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current Terms and Conditions of Sales and delivery. Users must refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

Document No. OLYAUG24DATA



**National Sales and Technical Support:**  
 (07) 3807 3666  
 sales@a1rubber.com  
[www.a1rubber.com](http://www.a1rubber.com)



**UPCYCLED  
 AUSTRALIAN  
 TYRES**