

VISIPOL

DATA SHEET

Effective November 03, 2022

Product Overview

Visipol is a water-borne single part VOC compliant multipurpose resilient flooring adhesive. Visipol was especially formulated for the installation of rubber flooring in sheet and tile format (in dry areas) to most common interior sub-floors.

Visipol is water based, spreads easily, economical, excellent age resistance and has aggressive grab.

Visipol is available in 15 litre pails.

Specifications

Material	Single part flooring adhesive
Colour	milky
Working Time	Approx. 15-20min
Dry time	At 25°C: touch dry 45 mins, dry to handle 2 hours, hard dry 24 hours, full cure 7 days
Coverage	3.0-5.0m ² /L
VOC Content	compliant
Specific Gravity	1.25
pH	8
RH resistance	85% and falling

- Clean up with water
- See installation guide for application data

Adhering rubber flooring to substrates in indoor applications where the installation temperature is between 10 - 25 degrees Celcius and where the installation is not exposed to direct or indirect sunlight, heat or moisture. Uneven or damaged floors should be repaired with a cementitious levelling compound.

Application

Apply Visipol with a V2 notched trowel or as product specification. Apply an even coat to a manageable area. Allow the adhesive to tack up before installing the floor-covering. In humid or cold conditions ensure that the adhesive has sufficient tack before laying the floor-covering. Roll the floor-covering to manufacturer's instructions. Do not allow heavy traffic within 24 hours after installing the floor-covering.

Disclaimer

The above information is derived from periodic tests taken on actual product from the manufacturing process. Some variances in specifications and raw surface appearances are possible due to the use of recycled materials and our manufacturing tolerances. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The recommendation relating to the application and end use of A1 Rubbers products, are given in good faith, based on A1 Rubbers current knowledge and experience of the product when properly stored, handled and applied under normal conditions in accordance with A1 Rubbers recommendations. The user of the product must test the product's suitability for intended application and purpose. A1 Rubber reserves the right to change the properties and tolerances of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current Terms and Conditions of Sales and delivery. Users must refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

Document No. VISNOV22DATA



National Sales and Technical Support:
 (07) 3807 3666
 sales@a1rubber.com
 www.a1rubber.com



UPCYCLED
AUSTRALIAN
TYRES